



Insight Technology Pvt. Ltd.
UN Park, Jwagal, Lalitpur
Phone : 01 5260730
Cell: 9841538467 [whatsApp, Viber]
Sales : 9801148550
E-mail: care@insightinfosys.com
Web: <http://insightinfosys.com/>

Specification

Mimosa Surges Protector NID

FlexiMount XL	<ul style="list-style-type: none">• Weight: 0.60 kg (21.3 oz) • Mounting Base: 45 mm (1.77") x 127 mm (5.0") • Pole Length: 190 mm (7.5")• Pole Outside Diameter: 38 mm (1.5") • Articulation Angle: 180° • Mounting Options: Pole mount with two pipe clamp or surface mount with two screw hole points• Assembly: Pre-assembled with a white powder coated finish; Mounting screws and pipe/hose clamps not included• Recommended For: C5x (native 8 dBi) C5x + N5-x12 Horn C5x + N5-x16 Horn C5x + N5-x20 Dish C5x + N5-x25 Dish B24
Vertical Poles	The FlexiMounts come assembled, ready for vertical pole configurations, using the indicated pipe clamp slots in the diagram above.
Angled and Flat Poles	The FlexiMounts can be mounted in any orientation on angled and flat poles. To pivot the articulation direction, rotate the mounting base to the desired orientation.
Flat Surfaces	The FlexiMounts include two (2) convenient mounting screw hole points, allowing mounting to any vertical, sloped or horizontal surface.